

1) IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Product Name	S-A-S Clear Grease
Product No	SAS18 - 500 ml Aerosol
Supplier	Van-Line Ltd, Gelderd Road, Leeds, LS12 6NA.
Telephone	+44 (0)113 213 4300
Fax	+44 (0)113 213 4319
Email	contact@van-line.co.uk

2) HAZARDS IDENTIFICATION

CLASSIFICATION (1999/45)	Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. F+;R12. R52/53.
--------------------------	---

3) COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
ISOBUTANE	200-857-2	75-28-5	10-30%	F+;R12
MINERAL OIL (REFINED)	265-155-0	64742-52-5	30-60%	-
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT	265-151-9	64742-49-0	10-30%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
PROPANE	200-827-9	74-98-6	10-30%	F+;R12

4) FIRST AID MEASURES

General information	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.
Ingestion	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.
Skin contact	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
Eye contact	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5) FIRE-FIGHTING MEASURES

Extinguishing media	Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
Special fire fighting procedures	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
Unusual fire & explosion hazards	Aerosol cans may explode in a fire.

6) ACCIDENTAL RELEASE MEASURES

Spill clean up methods	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.
------------------------	---

7) HANDLING AND STORAGE

Handling precautions	Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
Storage precautions	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs	STEL - 15 Min	Notes
BUTANE	WEL	600 ppm	1450 mg/m ³	750 ppm 1810 mg/m ³
ISOBUTANE	WEL	800 ppm		800 ppm
MINERAL OIL (REFINED)			5 mg/m ³	10 mg/m ³
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT			1200 mg/m ³	
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating

WEL = Workplace Exposure Limit.

Ingredient comments

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

Protective equipment



Engineering measures Respiratory protection

Provide adequate general and local exhaust ventilation.
No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9) PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Aerosol.
Colour	Typical.
Odour	Characteristic.
Flammability limit - Lower (%)	0.8
Flammability limit - Upper (%)	9.0

10) STABILITY AND REACTIVITY

Stability	Stable under normal temperature conditions.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.
Haz. decomp. products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11) TOXICOLOGICAL INFORMATION

Inhalation	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
Skin contact	Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin.
Eye contact	Irritating to eyes. May cause chemical eye burns.
Route of entry	Inhalation. Skin and/or eye contact.

12) ECOLOGICAL INFORMATION

Ecotoxicity	Dangerous for the environment if discharged into watercourses.
--------------------	--

13) DISPOSAL CONSIDERATIONS

Disposal methods	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
-------------------------	---

14) TRANSPORT INFORMATION

Proper shipping name	Aerosols
Environmentally	No.
Hazardous Substance/Marine Pollutant	
UN No. ROAD	1950
ADR class No.	2
ADR class	Class 2: Gases
ADR pack group	Not Applicable
ADR label No.	2.1
UN No. sea	1950
IMDG CLASS	2.1
IMDG pack gr.	Not Applicable
EMS	F-D, S-U
UN No. air	1950
Air class	2.1
Air pack gr.	Not Applicable



15) REGULATORY INFORMATION

Labelling



Extremely flammable.

Risk phrases	R12: Extremely flammable. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

Safety phrases	S2 Keep out of the reach of children. S16 Keep away from sources of ignition - No smoking. S23 Do not breathe vapour/spray. S60 This material and its container must be disposed of as hazardous waste. S51 Use only in well-ventilated areas.
-----------------------	--

UK Regulatory references	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. The Control of Substances Hazardous to Health Regulations 2002.
---------------------------------	--

Statutory instruments	The Control of Substances Hazardous to Health Regulations 2002.
------------------------------	---

Approved code of practice	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.
----------------------------------	---

Guidance notes	Classification and Labelling of Substances and Preparations Dangerous for Supply. Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).
-----------------------	---

16) OTHER INFORMATION

Risk phrases in full	R12 Extremely flammable. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: May cause lung damage if swallowed. R11 Highly flammable R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 Vapours may cause drowsiness and dizziness.
-----------------------------	--